



# **XHUD1000 Quick Start**

**For XHUD1000 & XGPS190 with Apple**

- 1. Turn on the XGPS190 and choose your XGPS190 under the Bluetooth list from the iPad settings.**
- 2. Power up XHUD1000. Dual logo will appear on HUD screen. After logo disappears, open Dual ADS-B Status Tool app.**
- 3. Go to HUDControl tab of app, and tap the “XHUD” switch to connect HUD.**
- 4. Tap “Bluetooth” and choose the XGPS190.**

**Your HUD should now be connected. You can select AHRs, Traffic, and other settings from HUD Control Tab.**



# **XHUD1000 Firmware**

## **update steps for Apple devices**

### **Reminders:**

- **When updating firmware, ONLY HUD and Apple device should be powered on. Do not power up portable GPS receiver or other devices.**
  - **Ensure that WiFi and Bluetooth are enabled in Apple device, and that Apple device is connected to internet.**
  - **Do not unplug HUD during firmware update process.**
- 
- 1. Power up XHUD1000. Dual logo will appear on HUD screen for a few seconds. After logo disappears, open Dual ADS-B Status Tool app.**
  - 2. Select HUDControl tab, and tap 'XHUD' to connect your HUD.**
  - 3. Tap 'HUD Software Version'.**
  - 4. Tap 'Download and Install' and follow the instructions on Apple device. Loading will take several minutes.**